


Model: CL3421NZ (non-rotating)	
Base tube diameter:	3.54" (90mm)
Number of sections:	Four
Extended Height:	17'
Retracted Height:	68"
Max top load:	55 lbs.
Max wind speed:	60 mph @ 372 sq. in.
Internal Cable Option "Z":	(9)16ga + (13)24ga



- Tower features an upper tubular protection cover that keeps dust and water away from the seal rings when in the retracted position.
- Tower is suitable for mounting on vehicles and can accommodate floodlights, cameras or antennas.
- Tower comes equipped with our exclusive keyway system, which prevents tower rotation and damage in windy conditions.
- Tower is provided with pre-drilled lower mounting and upper head assembly brackets for equipment mounting.
- An air safety valve for over-pressure and condensation drainage is standard as are water drainage holes to avoid freezing at lower temperatures.
- Pneumatic height extension may be achieved from a manual hand pump system, compressed air supply from chassis air brakes, breathing air system or a small electric air compressor.
- During retraction, an integral pneumatic shock absorption system safely lowers the tower, protecting floodlights and other equipment mounted on the tower.
- Tower requires no routine lubrication. All internal lubrication is performed during assembly and is good for the life of the tower.




Tilt/Turn Option: 12V "Light" tilt/turn model TT31603. Features 355 degree rotation and "auto-stow" via remote control. Capacity: 33 lbs.

Refer to the Tempest Fireco Towers Catalog-103 for more detailed specifications and information.



Tower Mounting Brackets



**Tempest
Fireco
Towers**

FILE : 20287
SCALE - 1:10